

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>HAD119287</b>	
Approved On:	Approved By:
Approved On.	Аррголеч Бу.

## BL5016 LED Bullyte with Mounting Stake 7W By Hadco by Signify





## Description

BL5016 7 Watt 24 or 36 Degree Narrow Flood LED Aluminum Bullyte with Mounting Stake is fabricated from die cast marine grade aluminum alloy with fully adjustable swivel arm with vibration proof locking teeth and fully adjustable double gasketed shroud. Thermoset polyester powdercoat finish in Black or Bronze. Clear tempered glass affixed at 10 degree angle for natural cleaning. Includes 1.4 inch diameter x 9.5 inch length S7 PVC stake with integral .5 inch NPS fitter. Optional junction box accessories available, sold separately. One 7 watt 24 degree beam angle GU5.3 MR16 EnduraLED lamp included. Available with 3000K Warm White color temperature. Available in a 24 degree narrow flood beam spread option. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable not included. 2.8 inch diameter x 5.8 inches long. ETL listed for wet locations. Note: Required remote transformer and optional mounting accessories sold separately.

## Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Magnetic
DIMENSIONS
INTEGRATED LED MODULE 1 x MR16/GU5.3 (bipin)/7W/12V LED
Technical Information
BEAM ANGLE



Shown in bronze





CLICK TO VIEW PRODUCT

Notes: