Lightology

lightology.com
866-954-4489
10-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1200991**


Approved On: Approved By:

TruLine 1A 24VDC Tunable White Drywall Plaster-In System

By PureEdge Lighting

Description

The TruLine 1A Tunable White Plaster-In 24VDC LED system provides smooth and glare-free general illumination using designer-grade high CRI LEDs. TruLine 1A recesses within 5/8 inch drywall without any joist modification. The slim extrusions, LED strips, and lenses are field-cuttable. Includes 2, 5 or 7 watts/foot LED module in 2K6K 2000K-6500K Tunable White color temperature option. Included components: Junction Box, Adjustable Mounting Bars, TruLine 1A Channel(s), End Cap, Take-Up Box, Mounting Straps, Drywall Screws, LED Soft Strip, and Lens (es). Can be installed on a single surface, join runs on multiple planes from wall to ceiling, or from one wall to an adjacent wall. Use TruLine 1A Build-It-Yourself (BIY) with pre-formed components to create desired configurations including mitered picture frame and outside or inside corners for room wrapping installations. Note: A DMX color changing power supply or 2XK 0-10V 2-Channel power supply is required and sold separately. 0-10V requires two dimmers --one for intensity and one for color temperature. DMX power supply must be used with PureEdge controller (CDMX1-2XK). Product is built to order



Shown in white

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	20W
DIMMER	N/A
DIMENSIONS	48"L x 2.65"W x 0.63"H
INTEGRATED LED MODULE	4 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2000K-6000K Tunable White
LUMENS/WATT	266.80
LUMINOUS FLUX	1334 lumens

CLICK TO VIEW PRODUCT

Notes: