

# Lightology

lightology.com  
866-954-4489  
02-13-26

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG1201003**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_


## TruLine .5A Static White 24VDC Drywall Plaster-In System

By PureEdge Lighting




### Description

The TruLine .5A 5W 24VDC Plaster-In 24VDC LED system provides smooth and glare-free general illumination using designer-grade high CRI LEDs. TruLine .5A recesses within 5/8 inch drywall without any joist modification. The slim extrusions, LED strips, and lenses are field-cuttable. Includes 5 watts/foot LED module in 2700K Static White, 3000K Static White, 2700K (to 1800K) Warm Dim or 3000K (to 1800K) Warm Dim color temperature options. Can be installed on a single surface, join runs on multiple planes from wall to ceiling, or from one wall to an adjacent wall. Use TruLine .5A Build-It-Yourself (BIY) with pre-formed components to create desired configurations including mitered picture frame and outside or inside corners for room wrapping installations. System requires a 24 volt electronic low voltage (ELV) PS-60L-ELV-24VDC power supply (ELV dimming) which fits inside junction box or remote Universal (UNI) power supply (TRIAC/ELV/0-10V dimming), sold separately. Note: Required power supply, dimmer, and optional mounting components sold separately. Product is built to order



Shown in white



### Specifications

COLOR . . . . . N/A  
BODY FINISH . . . . . White  
WATTAGE . . . . . 20W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 48"L x 2.45"W x 0.53"H  
INTEGRATED LED MODULE . . . . . 4 x LED/5W/24V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 95 CRI  
LAMP COLOR . . . . . 2700K  
LUMENS/WATT . . . . . 266.40  
LUMINOUS FLUX . . . . . 1332 lumens



CLICK TO VIEW PRODUCT

Notes: