

Lightology

lightology.com
866-954-4489
05-25-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG1201004**
 Approved On: _____ Approved By: _____

TruLine .5A Static White/Warm Dim Drywall Plaster-In System By PureEdge Lighting




Description

The TruLine .5A 5W 24VDC Plaster-In 24VDC LED system provides smooth and glare-free general illumination using designer-grade high CRI LEDs. TruLine .5A recesses within 5/8 inch drywall without any joist modification. The slim extrusions, LED strips, and lenses are field-cuttable. Includes 2, 5 or 7 watts/foot LED module in 2700K Static White, 3000K Static White, 2700K (to 1800K) Warm Dim or 3000K (to 1800K) Warm Dim color temperature options. Note: Warm Dim available in 5 watt option only. Can be installed on a single surface, join runs on multiple planes from wall to ceiling, or from one wall to an adjacent wall. System requires a 24 volt electronic low voltage (ELV) PS-60L-ELV-24VDC power supply (ELV dimming) which fits inside junction box or remote Universal (UNI) power supply (TRIAC/ELV/0-10V dimming), sold separately. Note: Required power supply, dimmer, and optional mounting components sold separately. Product is built to order



Shown in white



Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	30W
DIMMER	Low Voltage Electronic
DIMENSIONS	72"L x 2.45"W x 0.53"H
INTEGRATED LED MODULE	6 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K
LUMENS/WATT	399.60
LUMINOUS FLUX	1998 lumens



CLICK TO VIEW PRODUCT

Notes: