



## TruLine 1.6A 24VDC Plaster-In LED System

SPEC #

EDG1201023



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

### DESCRIPTION

The TruLine 1.6A, a versatile 24VDC linear plaster-in LED system, creates glare-free indoor architectural lighting. TruLine recesses into 5/8 inch drywall without any joist modification. The slim extrusions, LED strips, and lenses are field-cuttable. Includes 5 (2x2.5 watts) or 10 (2x5 watts) per foot LED with color temperature options in 2700K Static White, 3000K Static White, and 2700K or 3000K Warm Dim (to 1800K, in 10W/ft only). Can be run in vertical, horizontal and diagonal directions. Included components: TruLine 1.6A channel(s), LED Soft Strip, TL1.6A Junction Box, Take-Up Box, Adjustable Mounting Bars, Mounting Strap, Power End Cap, Drywall Screw, and Lenses. System requires a 24 volt electronic low voltage (ELV) PS-60L-ELV-24VDC power supply (ELV dimming) which fits inside junction box or remote Universal (UNI) power supply (TRIAC/ELV/0-10V dimming), sold separately. Note: Required power supply, dimmer, and optional mounting components sold separately. Product is built to order



Shown in: White


SHADE COLOR	N/A
BODY FINISH	White
WATTAGE	20W
DIMMER	Low Voltage Electronic
DIMENSIONS	48"L x 3.73"W x 0.63"H
INTEGRATED LED MODULE	
LAMP	4 x LED/5W/24V LED

#### Technical Information


LUMINOUS FLUX	1844 lumens
LUMENS/WATT	368.80
LAMP COLOR	2700K
LAMP LIFE	50000 hours

SPEC #

EDG1201023



#### INCLUDED COMPONENTS



- A. JUNCTION BOX**  
Mounts behind drywall with Adjustable Mounting Bars. Low Voltage 24VDC wires from Remote Power Supply connect to LED wires inside box. Junction Box opening is covered by the channel, and required at the beginning of each run.
- B. ADJUSTABLE MOUNTING BARS**  
Provide flexibility for mounting in a variety of spaces and orientations. May be secured to studs that are spaced 13"-24" apart.
- C. TRULINE 1.6A CHANNEL**  
5/8" deep extrusion housing for two rows of LED Soft Strip.
- D. POWER END CAP**  
Provides a finished look and prevents light leak at feed-end of runs where LED Soft Strip enters the channel.
- E. TAKE-UP BOX**  
Prevents dark spots at the end of a run by tucking excess LED Soft Strip safely behind wall.
- F. MOUNTING STRAP**  
Secures channel to drywall when wall stud is unavailable.
- G. DRYWALL SCREW**  
Secures channel to drywall and stud.
- H. LED SOFT STRIP**  
Commercial-grade white or color-changing LED Soft Strip. TruLine 1.6A comes with two LED Soft Strips.
- I. LENS**  
1.6" wide diffused white lens projects a clean line of light without LED dots.

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE