

Lightology

lightology.com
866-954-4489
07-06-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **LCF1204269**

Approved On: _____ Approved By: _____

Atomos 2 Slim Round Trimless Wood / IC Airtight Housing By Lucifer Lighting



Description

The Atomos 2 Slim Round Trimless Downlight for Wood Ceilings with New Construction IC Airtight Housing features a low profile baffle and slim housing that is perfect for residential, retail or commercial spaces. The powdercoated aluminum baffle complement any interior. Includes a soft focus lens. Available with 15 or 50 degree beam optic in 2700K, 3000K, or Warm Dim (3000K - 1800K) color temperatures. Integral 120 volt LED driver dimmable with an electronic low voltage (ELV) or Triac dimmer to 1%.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Satin Silver
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	13"L x 7.5"W x 3.4"H
INTEGRATED LED MODULE	1 x LED/15W/120V LED

Technical Information

APERTURE SIZE	2.00"
APERTURE SHAPE	Round
HOUSING HEIGHT	3.5"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Wood
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	15°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	66.00
LUMINOUS FLUX	990 lumens



Shown in satin silver



CLICK TO VIEW PRODUCT

Notes: