

Lightology

lightology.com
866-954-4489
07-01-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **WAC1205980**
Approved On: _____ Approved By: _____

FQ 2IN 15W Shallow Round Adjustable Trimless Downlight

By WAC Lighting



Description

The FQ 2IN 15W Shallow Round Adjustable Trimless Downlight is designed for use with FQ 2IN Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. The trim ships with a 25 degree reflector pre-installed, but also includes field-changeable 40 and 55 degree reflectors for a wider beam angle. The luminaire can be tilted up to 35 degrees and rotated 360 degrees to aim the light precisely where it is needed. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. Note: The Warm Dim luminaire is not available with 25 degree beam spread. It is shipped with a 40 degree reflector pre-installed and includes a field-changeable 50 degree reflector. A complete fixture requires the trim and a housing, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	2.75"W x 3.88"H
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED

Technical Information

APERTURE SIZE	2.750"
APERTURE SHAPE	Round
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	25°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	73.67
LUMINOUS FLUX	1105 lumens



Shown in white



3 7/8"

2 3/4"



CLICK TO VIEW PRODUCT

Notes: