

# Lightology

lightology.com  
866-954-4489  
04-09-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC1206010**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 2 inch Round Trimless Adjustable Downlight Trim By WAC Lighting



### Description

The FQ 2 Inch Round Trimless Adjustable Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 365 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V. Dimmable with 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

### Specifications

REFLECTOR/BAFFLE COLOR . . . . . N/A  
 BODY FINISH . . . . . Dark Bronze  
 WATTAGE . . . . . 25W  
 DIMMER . . . . . Low Voltage Electronic  
 DIMENSIONS . . . . . 2.75"W x 5"H  
 INTEGRATED LED MODULE . . . . . 1 x LED/25W/120-277V LED

### Technical Information

APERTURE SHAPE . . . . . Round  
 CEILING TYPE . . . . . Drywall Trimless/Flush  
 FUNCTION . . . . . Adjustable Accent  
 LAMP LIFE . . . . . 50000 hours  
 BEAM ANGLE . . . . . 40°  
 COLOR RENDERING . . . . . 90 CRI  
 LAMP COLOR . . . . . 3500K  
 LUMENS/WATT . . . . . 74.60  
 LUMINOUS FLUX . . . . . 1865 lumens



Shown in dark bronze

Model	Beam	% Lumens	°CRP	Color Temp	CF	Finishes	Reflector/Trim
K3PRA1 Recessed Trimless	N 25°	1735	4500	927	2700K	90	BK DB HC WT
	F 40°	1865	3000				
	W 55°	1795	2180				
K3PRA1	N 25°	1865	4500	935	3000K	90	BK DB HC WT
	F 40°	1785	3035				
	W 55°	1795	2395				
K3PRA1	N 25°	1865	4515	935	3000K	90	BK DB HC WT
	F 40°	1830	3115				
	W 55°	1830	2340				

Field changeable beam angle with reflectors provided  
 (25 degree/40 degree/55 degree)  
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: