

Lightology

lightology.com
866-954-4489
05-24-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206012** _____
 Approved On: _____ Approved By: _____

FQ 2 inch Round Adjustable Trimless Downlight By WAC Lighting



Description

The FQ 2 Inch Round Trimless Adjustable Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 365 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V. Dimmable with 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	2.75"W x 5"H
INTEGRATED LED MODULE	1 x LED/120-277V LED

Technical Information

APERTURE SHAPE	Round
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMINOUS FLUX	1865 lumens



Shown in white

Model	Beam	° Lumens	° CRI	Color Temp	CF	Finishes	Reflector/Trim
K2PRA1 Recessed Trimless	H 25°	1735	4000	927	2700K	90	BK DB HC WT
	F 40°	1865	3000				
	W 55°	1795	2180				
K2PRA1	H 25°	1865	4000	935	3000K	90	BK DB HC WT
	F 40°	1785	3035				
	W 55°	1795	2395				

Field changeable beam angle with reflectors provided
(25 degree/40 degree/55 degree)
Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: