

Lightology

lightology.com
866-954-4489
04-04-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206014**
 Approved On: _____ Approved By: _____

FQ 2 inch Round With Trim Adjustable Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Round With Trim Adjustable Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 365 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V. Dimmable with 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Dark Bronze
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 5"H
INTEGRATED LED MODULE	1 x LED/25W/120-277V LED

Technical Information

APERTURE SHAPE	Round
CEILING TYPE	Drywall with Trim
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMENS/WATT	72.80
LUMINOUS FLUX	1820 lumens



Shown in dark bronze

Model	Beam	Lumens	°CRP	Color Temp	DR	Finish	Reflector/Trim
REFLECT Round Trim	25°	1715	4510	927	2700K	90	Black Dark Bronze Alpine/White
	40°	1695	2900				
	55°	1700	2180				
REFLECT Round Trim	25°	1825	4160	930	3500K	90	BK DB KW/WT
	40°	1785	3055				
	55°	1795	2515				
REFLECT Round Trim	25°	1865	4815	935	3500K	90	BK DB KW/WT
	40°	1820	3115				
	55°	1830	2340				

Field changeable beam angles (25/40/55 degree) - reflectors provided
Lumens shown based on 40degree beam angle at 25 watts



CLICK TO VIEW PRODUCT

Notes: