

Lightology

lightology.com
866-954-4489
04-21-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **WAC1206019**

Approved On: _____ Approved By: _____

FQ 2 inch 15W Shallow Round Trimless Downlight

By WAC Lighting



Description

The FQ 2 inch 15W Shallow Round Trimless Downlight is designed for use with FQ 2IN Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. The trim ships with a 25 degree reflector pre-installed, but also includes field-changeable 40 and 55 degree reflectors for a wider beam angle. A 30 degree shielding angle provides superior glare control. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. Note: The Warm Dim luminaire is not available with 25 degree beam spread. It is shipped with a 40 degree reflector pre-installed and includes a field-changeable 50 degree reflector. A complete fixture requires the trim and a housing, sold separately.

Specifications




REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Haze
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	2.75"W x 3.88"H
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED

Technical Information

APERTURE SIZE	2.750"
APERTURE SHAPE	Round
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	25°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	79.33
LUMINOUS FLUX	1190 lumens



Shown in haze



CLICK TO VIEW PRODUCT

Notes: