

Lightology

lightology.com
866-954-4489
07-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **WAC1206049**
Approved On: _____ Approved By: _____

FQ 2IN 25W Round Trimless Downlight

By WAC Lighting



Description

The FQ 2IN 25W Round Trimless Downlight is designed for use with FQ 2IN Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. The trim ships with a 25 degree reflector pre-installed, but also includes field-changeable 40 and 55 degree reflectors for a wider beam angle. A 30 degree shielding angle provides superior glare control. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. Note: A complete fixture requires the trim and a housing, sold separately.

Specifications


| | |
|------------------------|--------------------------|
| REFLECTOR/BAFFLE COLOR | N/A |
| BODY FINISH | Black |
| WATTAGE | 25W |
| DIMMER | Low Voltage Electronic |
| DIMENSIONS | 2.75"W x 3.88"H |
| INTEGRATED LED MODULE | 1 x LED/25W/120-277V LED |

Technical Information

| | |
|-----------------|------------------------|
| APERTURE SIZE | 2.750" |
| APERTURE SHAPE | Round |
| CEILING TYPE | Drywall Trimless/Flush |
| FUNCTION | Downlight |
| LAMP LIFE | 50000 hours |
| BEAM ANGLE | 25° |
| COLOR RENDERING | 90 CRI |
| LAMP COLOR | 3500K |
| LUMENS/WATT | 83.40 |
| LUMINOUS FLUX | 2085 lumens |



Shown in black



5"

2 3/4"



CLICK TO VIEW PRODUCT

Notes: