

Lightology

lightology.com
866-954-4489
04-24-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206049**
 Approved On: _____ Approved By: _____

FQ 2 inch Round Trimless Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Round Trimless Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR N/A
 BODY FINISH Black
 WATTAGE 25W
 DIMMER Low Voltage Electronic
 DIMENSIONS 2.75"W x 5"H
 INTEGRATED LED MODULE 1 x LED/25W/120-277V LED

Technical Information

APERTURE SHAPE Round
 CEILING TYPE Drywall Trimless/Flush
 FUNCTION Downlight
 LAMP LIFE 50000 hours
 BEAM ANGLE 40°
 COLOR RENDERING 90 CRI
 LAMP COLOR 3500K
 LUMENS/WATT 82.60
 LUMINOUS FLUX 2065 lumens



Shown in black

Model	Beam	Lumens	CRI	Color Temp	CR	Finishes	Reflector/Trim
R2PFDL Recessed Downlight	N 25°	1870	90	5016	927	2700K	90
	F 40°	1815	90	2425			
	W 55°	1625	90	2620			
R2PFDL	N 25°	2041	90	5610	930	3000K	90
	F 40°	2025	90	3700			
	W 55°	1900	90	2925			
R2PFDL	N 25°	2081	90	5725	935	3500K	90
	F 40°	2055	90	3865			
	W 55°	2040	90	3535			

Field changeable beam angle with reflectors provided
 (25 degree/40 degree/55 degree)
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: