

# Lightology

lightology.com  
866-954-4489  
07-01-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC1206049**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 2 inch Round Trimless Downlight By WAC Lighting



### Description

The FQ 2 Inch Round Trimless Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

### Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	2.75"W x 5"H
INTEGRATED LED MODULE	1x LED/120-277V LED

### Technical Information

APERTURE SHAPE	Round
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	.90 CRI
LAMP COLOR	.3500K
LUMINOUS FLUX	2065 lumens



Shown in black

Model	Beam	Lumens	CRI	Color Temp	CRI	Finishes	Reflector/Trim	
R2PFDL Recessed Downlight	N 25°	1870	90	5016	90	BK DB HC WT	Black Charl Bronze Pearl White	
	F 40°	1815	2425	927				2700K
	W 55°	1625	2620					
R2PFDL	N 25°	2041	5610		90	BK DB HC WT	Black Charl Bronze Pearl White	
	F 40°	2025	3700	930				3000K
	W 55°	1900	3925					
R2PFDL	N 25°	2081	5725		90	BK DB HC WT	Black Charl Bronze Pearl White	
	F 40°	2055	3865	935				3000K
	W 55°	2040	4035					

Field changeable beam angle with reflectors provided  
 (25 degree/40 degree/55 degree)  
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: