

# Lightology

lightology.com  
866-954-4489  
04-22-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC1206053**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 2 inch Round With Trim Downlight Trim By WAC Lighting



### Description

The FQ 2 Inch Round With Trim Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

### Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 5"H
INTEGRATED LED MODULE	1 x LED/25W/120-277V LED

### Technical Information

APERTURE SHAPE	Round
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMENS/WATT	82.60
LUMINOUS FLUX	2065 lumens



Shown in black

Model	Beam	Lumens	°CRP	Color Temp	ELV	Finish	Reflector/Trim
FQ20T Round Trim	25°	1940	2510	927	2700K	90	Black Black Baffle Black/White White
	40°	3225	3420				
	55°	4830	2670				
FQ20T Round Trim	25°	2045	5610	930	3000K	90	BK CR HW WT
	40°	2625	3760				
	55°	3930	2970				
FQ20T Round Trim	25°	2065	5725	935	3000K	90	BK CR HW WT
	40°	2955	3865				
	55°	4310	3035				

Field changeable beam angles (25/40/55 degree) - reflectors provided  
Lumens shown based on 40degree beam angle at 25 watts



CLICK TO VIEW PRODUCT

Notes: