

Lightology

lightology.com
866-954-4489
07-02-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **WAC1206102**
Approved On: _____ Approved By: _____

FQ 2IN 15W Shallow Square Adjustable Trimless Downlight By WAC Lighting



Description

The FQ 2IN 15W Shallow Square Adjustable Trimless Downlight is designed for use with FQ 2IN Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. The trim ships with a 25 degree reflector pre-installed, but also includes field-changeable 40 and 55 degree reflectors for a wider beam angle. The luminaire can be tilted up to 35 degrees and rotated 360 degrees to aim the light precisely where it is needed. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. Note: The Warm Dim luminaire is not available with 25 degree beam spread. It is shipped with a 40 degree reflector pre-installed and includes a field-changeable 50 degree reflector. A complete fixture requires the trim and a housing, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Dark Bronze
WATTAGE 15W
DIMMER Low Voltage Electronic
DIMENSIONS 2.25"W x 3.63"H
INTEGRATED LED MODULE 1 x LED/15W/120-277V LED

Technical Information

APERTURE SIZE 2.500"
APERTURE SHAPE Square
CEILING TYPE Drywall Trimless/Flush
FUNCTION Adjustable Accent
LAMP LIFE 50000 hours
BEAM ANGLE 25°
COLOR RENDERING 90 CRI
LAMP COLOR 2700K
LUMENS/WATT 74.00
LUMINOUS FLUX 1110 lumens



Shown in dark bronze



3 5/8"

2 1/4"



CLICK TO VIEW PRODUCT

Notes: