

Lightology

lightology.com
866-954-4489
02-09-26

Project:

Company:

Location:

Fixture Type:

SPEC #: **WAC1206135**

Approved On:

Approved By:

FQ 2 inch Square Trimless Adjustable Downlight Trim

By WAC Lighting



Description

The FQ 2 Inch Square Trimless Adjustable Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 365 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V. Dimmable with 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Haze
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	2.25"W x 4.75"H
INTEGRATED LED MODULE	1x LED/25W/120-277V LED

Technical Information

APERTURE SHAPE	Square
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMENS/WATT	74.20
LUMINOUS FLUX	1855 lumens



Shown in haze

Model	Beam	*Lumens	*CRI	Color Temp	CRI	Finishes	Reflector/Trim
RDF5AL	40°	1740	4400	2700K	90	BK	Black
	25°	1720	2500			DB	Dark Bronze
	55°	1740	2500			HB	Heirloom Bronze
	40°	1830	4225	3000K	90	WT	White
	25°	1830	4225	3000K	90		
	55°	1830	2315				
	40°	1875	4620	3500K	90		
	25°	1875	4620	3500K	90		
	55°	1870	2365				

Field changeable beam angle with reflectors provided
(25 degree/40 degree/55 degree)
Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: