

Lightology

lightology.com
866-954-4489
05-15-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206135**
 Approved On: _____ Approved By: _____

FQ 2 inch Square Adjustable Trimless Downlight By WAC Lighting



Description

The FQ 2 Inch Square Trimless Adjustable Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 365 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V. Dimmable with 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Haze
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	2.25"W x 4.75"H
INTEGRATED LED MODULE	1x LED/120-277V LED

Technical Information

APERTURE SHAPE	Square
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMINOUS FLUX	1855 lumens



Shown in haze

Model	Model	Beam	Lumens	°CRP	Color Temp	CR	Finish	Reflector/Trim
	R2FSAL Square Trimless	N 25°	1745	4490	927	2700K	90	BK Black DB Dark Bronze MC Matte WT White
		F 40°	1725	2000				
		W 55°	1740	2000				
		N 25°	1835	4725	930	3000K	90	
		F 40°	1820	3075				
		W 55°	1830	2115				
N 25°	1815	4824	935	3000K	90			
F 40°	1815	2115						
W 55°	1810	2345						

Field changeable beam angle with reflectors provided
 (25 degree/40 degree/55 degree)
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: