

Lightology

lightology.com
866-954-4489
04-12-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206140**
 Approved On: _____ Approved By: _____

FQ 2 inch Square With Trim Adjustable Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Square With Trim Adjustable Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 365 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V. Dimmable with 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 4.75"H
INTEGRATED LED MODULE	1 x LED/25W/120-277V LED

Technical Information

APERTURE SHAPE	Square
CEILING TYPE	Drywall with Trim
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMENS/WATT	74.20
LUMINOUS FLUX	1855 lumens



Shown in white

Model	Beam	*lumens	*C/CP	Color Temp	CFI	Finish	Reflector/Trim
FQ25AT Adjustable Trim	25°	1745	4400	937	2700K	90	BK DB WHT
	40°	1725	2500				
	55°	1740	2200				
FQ25AT	25°	1855	4725	930	3500K	90	BK DB WHT
	40°	1830	3075				
	55°	1830	2375				
FQ25AT	25°	1875	4830	935	3500K	90	BK DB WHT
	40°	1855	3135				
	55°	1870	2465				

Field changeable beam angles (25/40/55 degree) - reflectors provided
Lumens shown based on 40degree beam angle at 25 watts



CLICK TO VIEW PRODUCT

Notes: