

# Lightology

lightology.com  
866-954-4489  
07-02-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **WAC1206144**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 2IN 15W Shallow Square Trimless Downlight

By WAC Lighting



### Description

The FQ 2IN 15W Shallow Square Trimless Downlight is designed for use with FQ 2IN Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. The trim ships with a 25 degree reflector pre-installed, but also includes field-changeable 40 and 55 degree reflectors for a wider beam angle. A 30 degree shielding angle provides superior glare control. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. Note: The Warm Dim luminaire is not available with 25 degree beam spread. It is shipped with a 40 degree reflector pre-installed and includes a field-changeable 50 degree reflector. A complete fixture requires the trim and a housing, sold separately.

### Specifications


REFLECTOR/BAFFLE COLOR . . . . . N/A  
BODY FINISH . . . . . White  
WATTAGE . . . . . 15W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 2.25"W x 3.63"H  
INTEGRATED LED MODULE . . . . . 1 x LED/15W/120-277V LED

### Technical Information

APERTURE SIZE . . . . . 2.500"  
APERTURE SHAPE . . . . . Square  
CEILING TYPE . . . . . Drywall Trimless/Flush  
FUNCTION . . . . . Downlight  
LAMP LIFE . . . . . 50000 hours  
BEAM ANGLE . . . . . 25°  
COLOR RENDERING . . . . . 90 CRI  
LAMP COLOR . . . . . 2700K  
LUMENS/WATT . . . . . 79.67  
LUMINOUS FLUX . . . . . 1195 lumens



Shown in white



3 5/8"

2 1/4"



CLICK TO VIEW PRODUCT

Notes: