

Lightology

lightology.com
866-954-4489
10-14-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **WAC1206173**
Approved On: _____ Approved By: _____

FQ 2 inch Square Trimless Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Square Trimless Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Black
WATTAGE 25W
DIMMER Low Voltage Electronic
DIMENSIONS 2.25"W x 4.75"H
INTEGRATED LED MODULE 1 x LED/25W/120-277V LED

Technical Information

APERTURE SHAPE Square
CEILING TYPE Drywall Trimless/Flush
FUNCTION Downlight
LAMP LIFE 50000 hours
BEAM ANGLE 40°
COLOR RENDERING 90 CRI
LAMP COLOR 3500K
LUMENS/WATT 79.60
LUMINOUS FLUX 1990 lumens



Shown in black

	Model	Beam	Lumens	"COP"	Color Temp	CR	Finish	Reflector/Trim	
	R23DFSL Square Trimless	H 25°	1880	4713	927	2700K	90	BK DB HL WT	Black Crown Bronze Aluz White
		F 40°	1880	2115					
		W 55°	1880	2400					
		H 25°	1990	5000	930	3000K	90		
		F 40°	1990	2275					
		W 55°	1990	2525					
		H 25°	2020	5105	935	3500K	90		
		F 40°	1990	2345					
		W 55°	1990	2525					

Field changeable beam angle with reflectors provided
(25 degree/40 degree/55 degree)
Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: