

Lightology

lightology.com
866-954-4489
05-12-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206173**
 Approved On: _____ Approved By: _____

FQ 2 inch Square Trimless Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Square Trimless Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR N/A
 BODY FINISH Black
 WATTAGE 25W
 DIMMER Low Voltage Electronic
 DIMENSIONS 2.25"W x 4.75"H
 INTEGRATED LED MODULE 1 x LED/25W/120-277V LED

Technical Information

APERTURE SHAPE Square
 CEILING TYPE Drywall Trimless/Flush
 FUNCTION Downlight
 LAMP LIFE 50000 hours
 BEAM ANGLE 40°
 COLOR RENDERING 90 CRI
 LAMP COLOR 3500K
 LUMENS/WATT 79.60
 LUMINOUS FLUX 1990 lumens



Shown in black

Model	Beam	*Lumens	*CFO	Color Temp	CRI	Finish(es)	Reflector/Trim
#2FSQL Square Trimless	N 25°	1880	4751	927	2700K	90	BC DB MC WT
	F 40°	1820	3115				
	W 55°	1860	2400				
#2FSQL Square Trimless	N 25°	1990	5051	930	3000K	90	BC DB MC WT
	F 40°	1920	3225				
	W 55°	1960	2520				
#2FSQL Square Trimless	N 25°	3020	7101	935	3000K	90	BC DB MC WT
	F 40°	1990	3341				
	W 55°	1990	2520				

Field changeable beam angle with reflectors provided
 (25 degree/40 degree/55 degree)
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: