

Lightology

lightology.com
866-954-4489
07-08-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206179**
 Approved On: _____ Approved By: _____

FQ 2 inch Square Downlight with Trim By WAC Lighting



Description

The FQ 2 Inch Square With Trim Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V, and 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White / Haze Reflector
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 4.75"H
INTEGRATED LED MODULE	1x LED/120-277V LED

Technical Information

APERTURE SHAPE	Square
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING90 CRI
LAMP COLOR3500K
LUMINOUS FLUX1990 lumens



Shown in white / haze reflector

Model	Beam	lumens	CRCP	Color Temp	CRP	Finishes	Reflector/Trim
BAFFLE Square Trim	W 35°	1860	4375				
	F 40°	1810	3115	927	2700K	90	
	W 55°	1860	2600				
	W 25°	1960	5005				Black
	F 40°	1950	3275	930	3000K	90	Dark Bronze Alpine White
	W 55°	1960	2575				White
W 25°	2620	5165					
	F 40°	1990	3345	935	3000K		
	W 55°	1995	2575				

Field changeable beam angles (25/40/55 degree) - reflectors provided
Lumens shown based on 40degree beam angle at 25 watts



CLICK TO VIEW PRODUCT

Notes: