

# Lightology

lightology.com  
866-954-4489  
05-17-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC1206250**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 4 inch Round Trimless Wall Wash By WAC Lighting



### Description

The FQ 4 inch Round Trimless Wall Wash is designed for use with FQ 4IN Series of recessed housings by WAC Lighting. This high performance LED luminaire will evenly illuminate a wall horizontally and vertically, and it is suitable for both commercial and residential applications. 360 degree rotation allows the light to be aimed precisely where it is needed. Ceiling cutout 4.75 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. Note: A complete fixture requires the trim and a housing, sold separately. Compatible with 13, 19, 25 and 28 watt housings.



Shown in haze

### Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Haze
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 5.63"H
INTEGRATED LED MODULE	LED/120-277V LED

### Technical Information

APERTURE SIZE	4.000"
APERTURE SHAPE	Round
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Wall Washer
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMINOUS FLUX	1980 lumens

Model	Beam	*Lumens	*CRP	Color Temp	CRI	Finishes	Reflector/Trim
BAFFWL Round Trimless	4	1842	N/A	927	90	DB CB MC WT	Black Clear Bronze Haze White
	4	1940	N/A	930	90		
	4	1980	N/A	935	90		

**BAFFWL** -  
Example: BAFFWL-930-WT  
\*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM		
	927	930	935
4	0.95	1.00	1.05
3	0.84	0.89	0.90
2	0.65	0.68	0.70
1	0.45	0.47	0.48

Example: BAFFWL-930-WT with 1 housing: 1940 lm (Reference Output) x 0.47 (Multiplier) = 910 lm

- Housing 1: 13 Watt
- Housing 2: 19 Watt
- Housing 3: 25 Watt
- Housing 4: 28 Watt



CLICK TO VIEW PRODUCT

Notes: