

Lightology

lightology.com
866-954-4489
05-12-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1206277**
 Approved On: _____ Approved By: _____

FQ 4 inch Square Trimless Wall Wash By WAC Lighting



Description

The FQ 4 Inch Square Trimless Wall Wash is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilting and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires the trim and a housing, sold separately. Compatible with 13, 19, 25 and 28 watt housings (lumens shown based on 3000K with a 28 watt housing)



Shown in dark bronze

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Dark Bronze
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	3"W x 5.63"H
INTEGRATED LED MODULE	LED/120-277V LED

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Wall Washer
LAMP LIFE	50000 hours
COLOR RENDERING	90 CRI
LAMP COLOR	3500K
LUMINOUS FLUX	1865 lumens

Model	Beam	*Lumens	CRI	Color Temp	CR	Finish	Reflector/Trim
R4FSWL Square Trimless	A	1770	N/A	927	2700K	90	
		1865	N/A	930	3000K	90	BL DB MC WT
		1900	N/A	935	3000K	90	Black Dark Bronze Haze White

R4FSWL Example: **R4FSWL-930-WT**

*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM		
	927	930	935
4	0.95	0.90	1.02
3	0.84	0.69	0.90
2	0.65	0.68	0.70
1	0.45	0.47	0.48

Example: **R4FSWL-930-WT** with 1 housing: 1865 lm (Reference Output) x 0.67 (Multiplier) = 955 lm

Housing 1: 13 Watt
 Housing 2: 19 Watt
 Housing 3: 25 Watt
 Housing 4: 28 Watt



CLICK TO VIEW PRODUCT

Notes: _____