Lightology

lightology.com
866-954-4489
10-30-26

Project:

Company:

Location: Fixture Type:

SPEC #: **DLS1231615**

Approved On: Approved By:

Notch Color-Select Regressed Panel Light


By DALS Lighting

Description

The Notch Regressed Panel Downlight is characterized by a deep-set LED position which greatly reduces glare, neatly packaged in a price-conscious solution to general lighting. Smooth 360 degree wide spread. Every fixture includes a junction box with an integrated driver. Can be daisy chained. Switch-selectable color temperature: 2700K/3000K/3500K/4000K/5000K with switch on panel wire. Frosted lens. Optional trims sold separately. 120V: TRIAC and ELV dimming (see attached manufacturer dimmer reference). 120-277V: 0-10V dimming.NOTE: 2 inch available in Black and White finishes. All other options available in White finish only.



Shown in white / white



Specifications

REFLECTOR/BAFFLE COLOR	White
BODY FINISH	White
WATTAGE	11W
DIMMER	Standard 120V
DIMENSIONS	4.75"W x 1.88"H
INTEGRATED LED MODULE	1 x LED/11W/120V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	3.810"
APERTURE SHAPE	Round
HOUSING HEIGHT	2"
HOUSING TYPE	Remodel IC Airtight
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	100°
COLOR RENDERING	90 CRI
LAMP COLOR	CCT Select
LUMENS/WATT	72.36
LUMINOUS FLUX	796 lumens

CLICK TO VIEW PRODUCT

Notes: