

# Lightology

lightology.com  
866-954-4489  
02-14-26

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **ELE12643**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Monorail 600W Dual Feed Surface Magnetic Transformer 12V

By Visual Comfort Architectural




### Description

The Monorail 600 Watt Dual Feed (2X300W) Magnetic Surface Mount Transformer converts standard 120 volt line voltage to 12 volts to provide the necessary voltage for powering a Monorail low-voltage lighting system. Transformer mounts to a standard 4 inch ceiling junction box with round plaster ring (provided by electrician). Isolating connectors included to isolate power 2X300 watts. Dimming coil included. The shortest rigid standoff that can be used with this surface transformer is the 5 inch rigid standoff, sold separately. If dropping the rail more than 5 inches below the ceiling, order the desired rigid standoff length and two compatible power extenders. ETL listed. 9.1 inch diameter x 5.8 inch height. Finish available in Satin Nickel ONLY. Image shown in White.



Shown in White

Shown in satin nickel



### Specifications

COLOR . . . . .	N/A
BODY FINISH . . . . .	Satin Nickel
WATTAGE . . . . .	600W
DIMMER . . . . .	Low Voltage Magnetic
DIMENSIONS . . . . .	9.1" W x 5.8" H
BULB . . . . .	N/A



CLICK TO VIEW PRODUCT

Notes: