



Cirrus Ceiling Channel D1 Lens w/Remote Power WET 68IN

SPEC #

EDG133600



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Cirrus Channel Ceiling Flush Wet Location features a direct flat lens with 100 degree beam spread. Includes 5 watts, 24 volt LED per foot with 2700K color temperature, 95+CRI LED. Finish available in Satin Black. Channel includes a split canopy that mounts on a standard junction box. May be ordered with a Slim Profile Channel Junction Box (C-TRE-JBOX), sold separately. Mounting clips (C-MCL) are included for use every 18 inches. Product is built to order. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Note: Required power supply, dimmer control, and optional accessories sold separately.



SHADE COLOR	N/A
BODY FINISH	Satin Black
WATTAGE	28.3W
DIMMER	0-10V
DIMENSIONS	68"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	
LAMP	LED/28.33W/24V LED

Technical Information


LUMINOUS FLUX	1331 lumens
LUMENS/WATT	46.98
LAMP COLOR	2700K
COLOR RENDERING	95 CRI
BEAM ANGLE	100°

SPEC #

EDG133600



Shown with C-TRE-JBOX (sold separately)



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE