



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Cirrus Channel Ceiling Flush Wet Location features a direct flat lens with 100 degree beam spread. Includes 5 watts, 24 volt LED per foot with 2700K color temperature, 95+CRI LED. Finish available in Satin Black. Channel includes a split canopy that mounts on a standard junction box. May be ordered with a Slim Profile Channel Junction Box (C-IRE-JBOX), sold separately. Mounting clips (C-MCL) are included for use every 18 inches. Can be powered using a Class 2 electronic low voltage, 0-10 volt or Lutron Hi-Lume power supply. In-wall mounting kits available for select power supplies. See attached manufacturer reference for dimmer compatibility. ETL listed. 5 year warranty. IP64 rated for covered areas in wet locations. Major components made and assembled in the USA. Required power supply and dimmer control sold separately. Product is built to order.




Shown in: Satin Black

SHADE COLOR	N/A
BODY FINISH	Satin Black
WATTAGE	28.33W
DIMMER	0-10V
DIMENSIONS	68" L x 0.9" W x 0.9" H
LAMP	LED/28.33W/24V LED

Technical Information

LUMINOUS FLUX	1331 lumens
LUMENS/WATT	46.98
LAMP COLOR	2700 K
COLOR RENDERING	95 CRI
BEAM ANGLE	100°

ITEM NUMBER EDG133600



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE