

# Lightology

lightology.com  
866-954-4489  
07-01-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **WAC1362186**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 4IN Round Downlight with Trim By WAC Lighting

### Description

The FQ 4 Inch Round Downlight with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features 30 degree shielding angle design for great visual comfort. Field changeable beam angle (2700K/3000K/3500K = 27/40/50 degree (27 degree pre-installed) / Warm Dim = 30/50 degree (30 degree pre-installed) with reflectors provided. Accepts one lens or glare control accessory. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. NOTE: A complete fixture requires a trim and a housing, sold separately. Refer to spec sheet for lumen calculation to determine wattage for housing.

### Specifications



COLOR . . . . . N/A  
BODY FINISH . . . . . Dark Bronze  
WATTAGE . . . . . N/A  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 5.5"W x 5.38"H  
BULB NOT INCLUDED . . . . . 1x LED/120-277V LED

### Technical Information

APERTURE SIZE . . . . . 4.000"  
APERTURE SHAPE . . . . . Round  
CEILING TYPE . . . . . Drywall with Trim  
FUNCTION . . . . . Downlight  
LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 90 CRI  
LAMP COLOR . . . . . 2700K  
LUMINOUS FLUX . . . . . 2370 lumens



Shown in dark bronze

2700K/3000K/3500K		WARM DIM	
			
<p><b>BEAM</b> . . . . .</p> <p>Beam angle is the angle between the beam of light and the axis of the beam. The beam angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>		<p><b>BEAM</b> . . . . .</p> <p>Beam angle is the angle between the beam of light and the axis of the beam. The beam angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>	
<p><b>SHIELDING</b> . . . . .</p> <p>Shielding angle is the angle between the beam of light and the axis of the beam. The shielding angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>		<p><b>SHIELDING</b> . . . . .</p> <p>Shielding angle is the angle between the beam of light and the axis of the beam. The shielding angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>	
<p><b>WATTAGE</b> . . . . .</p> <p>Wattage is the power consumed by the light source. The wattage is determined by the voltage and the current of the light source.</p>		<p><b>WATTAGE</b> . . . . .</p> <p>Wattage is the power consumed by the light source. The wattage is determined by the voltage and the current of the light source.</p>	
<p><b>BEAM</b> . . . . .</p> <p>Beam angle is the angle between the beam of light and the axis of the beam. The beam angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>		<p><b>BEAM</b> . . . . .</p> <p>Beam angle is the angle between the beam of light and the axis of the beam. The beam angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>	
<p><b>SHIELDING</b> . . . . .</p> <p>Shielding angle is the angle between the beam of light and the axis of the beam. The shielding angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>		<p><b>SHIELDING</b> . . . . .</p> <p>Shielding angle is the angle between the beam of light and the axis of the beam. The shielding angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>	
<p><b>WATTAGE</b> . . . . .</p> <p>Wattage is the power consumed by the light source. The wattage is determined by the voltage and the current of the light source.</p>		<p><b>WATTAGE</b> . . . . .</p> <p>Wattage is the power consumed by the light source. The wattage is determined by the voltage and the current of the light source.</p>	
<p><b>BEAM</b> . . . . .</p> <p>Beam angle is the angle between the beam of light and the axis of the beam. The beam angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>		<p><b>BEAM</b> . . . . .</p> <p>Beam angle is the angle between the beam of light and the axis of the beam. The beam angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>	
<p><b>SHIELDING</b> . . . . .</p> <p>Shielding angle is the angle between the beam of light and the axis of the beam. The shielding angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>		<p><b>SHIELDING</b> . . . . .</p> <p>Shielding angle is the angle between the beam of light and the axis of the beam. The shielding angle is determined by the beam spread of the light source and the distance from the light source to the surface being illuminated.</p>	
<p><b>WATTAGE</b> . . . . .</p> <p>Wattage is the power consumed by the light source. The wattage is determined by the voltage and the current of the light source.</p>		<p><b>WATTAGE</b> . . . . .</p> <p>Wattage is the power consumed by the light source. The wattage is determined by the voltage and the current of the light source.</p>	



CLICK TO VIEW PRODUCT

Notes: