

Lightology

lightology.com
866-954-4489
05-21-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362208**
 Approved On: _____ Approved By: _____

FQ 4 inch Round Warm Dim Wall Wash with Trim By WAC Lighting



Description

The FQ 4 Inch Round Warm Dim Wall Wash with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilt and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13 and 19 watt housings (lumens shown based on 19 watt housing)



Shown in white / haze reflector

Specifications

COLOR	N/A
BODY FINISH	White / Haze Reflector
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	5.5"W x 5.63"H
INTEGRATED LED MODULE	LED/120-277V LED

Technical Information

APERTURE SIZE	4.000"
APERTURE SHAPE	Round
CEILING TYPE	Drywall with Trim
FUNCTION	Wall Washer
LAMP LIFE	50000 hours
COLOR RENDERING	.90 CRI
LAMP COLOR	3000K Warm Dim
LUMINOUS FLUX	950 lumens

Model	Beam	*Lumens	*CRI	Color Temp	CR	Finish	Reflector/Trim	
	R4FRWT Round Dim	A Asym	550	N/A	WD	3000K-1800K SB	BE DB Haze WT WT	Black Dark Bronze Haze/White White

R4FRWT-WD
 Example: R4FRWT-WD-WT
 *Lumens shown in the table is a reference value for 90° beam with 2 housing. Use multiplier table below to determine the output for the other combination.

	Multiplier	TRIM
HOUSING	2	1.00
	1	0.69

Example: R4FRWT-WD-WT with 1 housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm

Housing 1: 13 Watt
 Housing 2: 19 Watt



CLICK TO VIEW PRODUCT

Notes: