

Lightology

lightology.com
866-954-4489
08-24-25

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362213**
 Approved On: _____ Approved By: _____

FQ 4 inch Round Wall Wash with Trim By WAC Lighting



Description

The FQ 4 Inch Round Wall Wash with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilt and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13, 19, 25 and 28 watt housings (lumens shown based 3000K with 28 watt housing)

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	5.5"W x 5.63"H
INTEGRATED LED MODULE	1x LED/120-277V LED

Technical Information

APERTURE SIZE	4.000"
APERTURE SHAPE	Round
CEILING TYPE	Drywall with Trim
FUNCTION	Wall Washer
LAMP LIFE	50000 hours
COLOR RENDERING	.90 CRI
LAMP COLOR	.2700K
LUMINOUS FLUX	.1940 lumens



Shown in white

Model	Beam	*Lumens	*CRI	Color Temp	CRI	Finishes	Reflector/Tim
	A	1940	N/A	927	2700K	90	
		1940	N/A	930	3500K	90	BK DB NCWT WT
		1980	N/A	935	3500K	90	

R4FRWT - ...
 Example: R4FRWT-930-WT
 *lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM		
	927	930	935
4	0.95	1.00	1.02
3	0.88	0.90	0.90
2	0.65	0.68	0.70
1	0.45	0.47	0.48

Example: R4FRWT-930-WT with 1 housing: 1940 lm (Reference Output) x 0.47 (Multiplier) = 910 lm

- Housing 1: 13 Watt
- Housing 2: 19 Watt
- Housing 3: 25 Watt
- Housing 4: 28 Watt



CLICK TO VIEW PRODUCT

Notes: