

Lightology

lightology.com
866-954-4489
06-15-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362233**
 Approved On: _____ Approved By: _____

FQ 4 inch Square Warm Dim Adjustable Downlight with Trim By WAC Lighting



Description

The FQ 4 inch Square Warm Dim Adjustable Downlight with Trim is designed for use with FQ 4IN Series of recessed housings by WAC Lighting. Features 0-45 degree vertical tilt and 365 degree horizontal rotation. Field adjustable beam angle 30 degree/50 degree reflectors provided (30 degree pre-installed) with Warm Dim (3000K-1800K) color temperature. Accepts one lens or glare control accessory. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13 and 19 watt housings (lumens shown based on 30 degree beam angle with 19 watt housing)

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	5.25"W x 5.63"H x 5.25"D
INTEGRATED LED MODULE	LED/120-277V LED

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
CEILING TYPE	Drywall with Trim
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
COLOR RENDERING	.90 CRI
LAMP COLOR	3000K Warm Dim
LUMINOUS FLUX	910 lumens



Shown in white

Model	Beam	*Lumens	*CRP	Color Temp	CRI	Finish	Reflector/Trim
R4FSAT Square Trim	F 30° W 50°	910 890	2941 1740	WD	3000K-1800K	90	BC DL HCWT WT

R4FSAT-WD...
 Example: R4FSAT-WD-BC (Beam F-30° reflector is pre-installed, Beam W-50° reflector is included)
 *Lumens and CRP are reference values for WD trim with a housing. Use multiplier table below to determine the output for the other combination.

	Multiplier	TRIM
HOUSING	2	1.00
	1	0.69

Example: R4FSAT-WD-WT with F-30° beam in 1 housing: 910 lm (Reference Output) x 0.69 (Multiplier) = 628 lm

Housing 1: 13 Watt
 Housing 2: 19 Watt



CLICK TO VIEW PRODUCT

Notes: