

Lightology

lightology.com
866-954-4489
06-29-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362258**
 Approved On: _____ Approved By: _____

FQ 4 inch Square Downlight with Trim By WAC Lighting



Description

The FQ 4 Inch Square Downlight with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features 30 degree shielding angle design for great visual comfort with 45 degree vertical tilt and 360 degree horizontal rotation. Field changeable beam angle (2700K/3000K/3500K = 27/40/50 degree (27 degree pre-installed). Accepts one lens or glare control accessory. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13, 19, 25 and 28 watt housings (lumens shown based on 27 degree beam angle at 3000K with 28 watt housing)

Specifications

COLOR N/A
 BODY FINISH Black
 WATTAGE N/A
 DIMMER Low Voltage Electronic
 DIMENSIONS 5.25"W x 5.25"H
 INTEGRATED LED MODULE LED/120-277V LED

Technical Information

APERTURE SIZE 3.000"
 APERTURE SHAPE Square
 CEILING TYPE Drywall with Trim
 FUNCTION Downlight
 LAMP LIFE 50000 hours
 COLOR RENDERING 90 CRI
 LAMP COLOR 2700K
 LUMINOUS FLUX 2445 lumens



Shown in black

Model	Beam	*Lumens	*CECF	Color Temp	CR	Finish	Reflector/Trim
R4FSOT Square Trim	W 27°	2325	3065	927	2700K	90	BK DB HWHT WT
	F 40°	2265	3190				
	W 50°	2285	3085				
	W 27°	2445	6710	930	3000K	90	
	F 40°	2385	7190				
	W 50°	2385	3245				
W 27°	2495	6230	935	3500K	90		
F 40°	2430	6615					
W 50°	2430	3310					

R4FSOT

Example: R4FSOT-927-BK (beam 27° reflector is pre-installed. Beams 40° and 50° reflectors are included)

*Lumens and CECF are reference values for 3000K beam in 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM		
	927	930	935
4	0.95	1.00	1.02
3	0.84	0.88	0.90
2	0.65	0.68	0.70
1	0.45	0.47	0.48

Example: R4FSOT-930-BK in 1 housing: 2445 lm (Reference Output) x 0.47 (Multiplier) = 1150 lm

Housing 1: 13 Watt
 Housing 2: 19 Watt
 Housing 3: 25 Watt
 Housing 4: 28 Watt



CLICK TO VIEW PRODUCT

Notes: