

# Lightology

lightology.com  
866-954-4489  
06-15-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC1362268**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 4 inch Square Warm Dim Trimless Wall Wash By WAC Lighting



### Description

The FQ 4 Inch Square Warm Dim Trimless Wall Wash Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will evenly illuminate a wall horizontally and vertically, and it is suitable for both commercial and residential applications. Designed for even wall illumination both vertically and horizontally. Warm Dim 3000K-1800K color temperature. Ceiling cutout: 4.75 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC at 120V, and 0-10V dimmers at 277V. Note: A complete fixture requires the trim and a housing, sold separately. Compatible with 13 watt and 19 watt housings.

### Specifications

COLOR	N/A
BODY FINISH	Black
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	3"W x 5.63"H
INTEGRATED LED MODULE	LED/120-277V LED

### Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Wall Washer
LAMP LIFE	50000 hours
COLOR RENDERING	.90 CRI
LAMP COLOR	3000K Warm Dim
LUMINOUS FLUX	950 lumens



Shown in black

Model	Beam	*Lumens	*CRP	Color Temp	CU	Finishes	Reflector/Trim
 <b>R4FSWL</b> Square Trimless	A	Align	950	4000K	90	<b>BL</b> <b>DB</b> <b>HL</b> <b>WT</b>	Black Dark Bronze Clear White

**R4FSWL** Example: **R4FSWL-WD-WT**  
 \*Lumens shown in the table is a reference value for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

HOUSING	Multiplier		TRIM	
	2	1	1.00	0.69
Example: <b>R4FSWL-WD-WT</b> with 1 housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm				

Housing 1: 13 Watt  
 Housing 2: 19 Watt



CLICK TO VIEW PRODUCT

Notes: