

Lightology

lightology.com
866-954-4489
05-16-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362281**
 Approved On: _____ Approved By: _____

FQ 4 inch Square Warm Dim Wall Wash with Trim By WAC Lighting



Description

The FQ 4 Inch Square Warm Dim Wall Wash with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilt and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Warm Dim (3000K-1800K) color temperature. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13 and 19 watt housings (lumens shown based on 19 watt housing)

Specifications

COLOR	N/A
BODY FINISH	Dark Bronze
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	5.25"W x 5.63"H x 5.25"D
INTEGRATED LED MODULE	LED/120-277V LED

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
CEILING TYPE	Drywall with Trim
FUNCTION	Wall Washer
LAMP LIFE	50000 hours
COLOR RENDERING	.90 CRI
LAMP COLOR	3000K Warm Dim
LUMINOUS FLUX	950 lumens



Shown in dark bronze

Model	Beam	*Lumens	*CCT	Color Temp	CRI	Finish	Reflector/Dim
R4FSWT Square Dim	A Apptm	950	N/A	WD 3000K-1800K	90	DC OR HOUT WT	Black Dark Bronze Pearl White White

R4FSWT-WD-__
 Example: R4FSWT-WD-WT
 *Lumens shown in the table is a reference value for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

	Multiplier	TBM
HOUSING	2	1.00
	1	0.69

Example: R4FSWT-WD-WT with 1 housing: 950 lm (Reference Output) x 0.69 (Multiplier) = 655 lm

Housing 1: 13 Watt
 Housing 2: 19 Watt



CLICK TO VIEW PRODUCT

Notes: