

# Lightology

lightology.com  
866-954-4489  
06-04-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC1362287**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## FQ 4 inch Square Wall Wash with Trim By WAC Lighting



### Description

The FQ 4 Inch Square Wall Wash with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilt and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13, 19, 25 and 28 watt housings (lumens shown based on 28 watt housing)



Shown in white

### Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	5.25"W x 5.63"H x 5.25"D
BULB NOT INCLUDED	LED/120-277V LED

### Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
CEILING TYPE	Drywall with Trim
FUNCTION	Wall Washer
LAMP LIFE	50000 hours
COLOR RENDERING	.90 CRI
LAMP COLOR	.2700K
LUMINOUS FLUX	.1775 lumens

Model	Beam	*Lumens	*CCT	Color Temp	CR	Finish	Reflector/Trim
R4FSWT Square Trim	A	1770	N/A	927	2700K	90	DR CR HCWT WT
	A	1865	N/A	930	3000K	90	DR CR HCWT WT
	A	1900	N/A	935	3500K	90	DR CR HCWT WT

R4FSWT...

Example: R4FSWT-930-WT

\*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM		
	927	930	935
4	0.95	1.00	1.02
3	0.84	0.88	0.90
2	0.65	0.68	0.70
1	0.65	0.67	0.68

Example: R4FSWT-930-WT with 1 housing: 1865 lm (Reference Output) x 0.47 (Multiplier) = 875 lm

- Housing 1: 13 Watt
- Housing 2: 19 Watt
- Housing 3: 25 Watt
- Housing 4: 28 Watt



CLICK TO VIEW PRODUCT

Notes: