

Lightology

lightology.com
866-954-4489
07-03-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **WAC1362287**
Approved On: _____ Approved By: _____

FQ 4IN Square Wall Wash with Trim By WAC Lighting



Description

The FQ 4 Inch Square Wall Wash with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilt and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable 100% to 1% with ELV, TRIAC, and 0-10V dimmers. NOTE: A complete fixture requires a trim and a housing, sold separately. Refer to spec sheet for lumen calculation to determine wattage for housing.

Specifications

COLOR N/A
BODY FINISH White
WATTAGE N/A
DIMMER Low Voltage Electronic
DIMENSIONS 5.25"W x 5.63"H x 5.25"D
BULB NOT INCLUDED 1x LED/120-277V LED

Technical Information

APERTURE SIZE 3.000"
APERTURE SHAPE Square
CEILING TYPE Drywall with Trim
FUNCTION Wall Washer
LAMP LIFE 50000 hours
COLOR RENDERING 90 CRI
LAMP COLOR 2700K
LUMINOUS FLUX 1775 lumens



Shown in white

| 2700K/3000K/3500K | | WARM DIM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---------|---|---------|---------|---------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|--|-------------|---------|---------|---------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| WATTAGE <table border="1"> <thead> <tr> <th>Beam Spread</th> <th>Wattage</th> <th>Wattage</th> <th>Wattage</th> </tr> </thead> <tbody> <tr> <td>10°</td> <td>1.0</td> <td>1.0</td> <td>1.0</td> </tr> <tr> <td>15°</td> <td>1.5</td> <td>1.5</td> <td>1.5</td> </tr> <tr> <td>20°</td> <td>2.0</td> <td>2.0</td> <td>2.0</td> </tr> <tr> <td>25°</td> <td>2.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>30°</td> <td>3.0</td> <td>3.0</td> <td>3.0</td> </tr> </tbody> </table> | | Beam Spread | Wattage | Wattage | Wattage | 10° | 1.0 | 1.0 | 1.0 | 15° | 1.5 | 1.5 | 1.5 | 20° | 2.0 | 2.0 | 2.0 | 25° | 2.5 | 2.5 | 2.5 | 30° | 3.0 | 3.0 | 3.0 | WATTAGE <table border="1"> <thead> <tr> <th>Beam Spread</th> <th>Wattage</th> <th>Wattage</th> <th>Wattage</th> </tr> </thead> <tbody> <tr> <td>10°</td> <td>1.0</td> <td>1.0</td> <td>1.0</td> </tr> <tr> <td>15°</td> <td>1.5</td> <td>1.5</td> <td>1.5</td> </tr> <tr> <td>20°</td> <td>2.0</td> <td>2.0</td> <td>2.0</td> </tr> <tr> <td>25°</td> <td>2.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>30°</td> <td>3.0</td> <td>3.0</td> <td>3.0</td> </tr> </tbody> </table> | | Beam Spread | Wattage | Wattage | Wattage | 10° | 1.0 | 1.0 | 1.0 | 15° | 1.5 | 1.5 | 1.5 | 20° | 2.0 | 2.0 | 2.0 | 25° | 2.5 | 2.5 | 2.5 | 30° | 3.0 | 3.0 | 3.0 |
| Beam Spread | Wattage | Wattage | Wattage | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10° | 1.0 | 1.0 | 1.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15° | 1.5 | 1.5 | 1.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20° | 2.0 | 2.0 | 2.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25° | 2.5 | 2.5 | 2.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30° | 3.0 | 3.0 | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Beam Spread | Wattage | Wattage | Wattage | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10° | 1.0 | 1.0 | 1.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15° | 1.5 | 1.5 | 1.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20° | 2.0 | 2.0 | 2.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 25° | 2.5 | 2.5 | 2.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30° | 3.0 | 3.0 | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SAFETY 4" FQ - Square Wall Wash Trim | | 4" FQ - Square Wall Wash Trim (Clear To Glass) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



CLICK TO VIEW PRODUCT

Notes: