

lightology.com 866-954-4489 09-01-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: WAC1362287	
Approved On:	Approved By:

FQ 4 inch Square Wall Wash with Trim By WAC Lighting







Description

The FQ 4 Inch Square Wall Wash with Trim is designed for use with FQ 4 Inch Series of recessed housings by WAC Lighting. Features glare control with 30 degree shielding, 45 degree vertical tilt and 360 degree horizontal rotation, and uniform floor-to-ceiling wall washing. Ceiling cutout: 4 3/4 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. NOTE: A complete fixture requires a trim and a housing, sold separately. Compatible with 13, 19, 25 and 28 watt housings (lumens shown based on 28 watt housing)

Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
BUILB NOT INCLUDED LED/120-277V LED

Technical Information

APERTURE SIZE
APERTURE SHAPE
CEILING TYPE
FUNCTION
LAMP LIFE
COLOR RENDERING
LAMP COLOR
LUMINOUS FLUX



Shown in white

		Model	Beam	*Lumens	*CBCP	Color	Гетр	CRI	Finishes	Reflector/Tri
W	T //			1770	N/A	927	2700K	90		
- 2x - - 2	i i	R4FSWT Square Trim	A Agm	1865	N/A	N/A 930	2000K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
				1900	N/A	935	3500K	90	1	
R4FSWT xample: R4FSW Lumens shown i	T-930-WT	e values for 3000K trim w			table belo	w to de	stermine the	output fo	r other cor	mbinations.
xample: R4FSW Lumens shown i	T-930-WT		ith 4 housing. U			w to de	termine the	output fo		
xample: R4FSW Lumens shown i	r-930-WT n the table are reference ultiplier	927			930		stermine the	output fo	935	
xample: R4FSW Lumens shown i	F-930-WT In the table are reference						stermine the	output fo		
xample: R4FSW Lumens shown i	r-930-WT n the table are reference ultiplier	927			930		stermine the	output fo	935	s 2
xample: R4FSW Lumens shown i	r-930-WT n the table are reference ultiplier	927 0.95			930		termine the	output fo	935	\$ 2



CLICK TO VIEW PRODUCT

Notes:	