

Lightology

lightology.com
866-954-4489
04-27-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362436**
 Approved On: _____ Approved By: _____

FQ 2 inch Round Warm Dim Trimless Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Round Warm Dim Trimless Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Warm Dim 3000K-1800K color temperature. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.



Shown in white

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	2.75"W x 5"H
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED

Technical Information

APERTURE SHAPE	Round
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K Warm Dim
LUMENS/WATT	64.33
LUMINOUS FLUX	965 lumens

Model	Beam	Lumens	CRP	Color Temp	CR	Finish	Reflector/Trim	
F	40°	965	1775	WD	3000K-1800K	90	RC DB MC WT	Black Dark Bronze Navy White
W	55°	950	1370					

Field changeable beam angle with reflectors provided
 (35 degree/40 degree/55 degree)
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: