

Lightology

lightology.com
866-954-4489
06-15-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362438**
 Approved On: _____ Approved By: _____

FQ 2 inch Round Warm Dim With Trim Downlight Trim By WAC Lighting



Description

The FQ 2 Inch Round With Trim Warm Dim Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Warm Dim 3000K-1800K color temperature. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. TRIAC and ELV dimming at 120V; 0-10V dimming at 277V. Note 1: Field changeable beam angle with reflectors provided (40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

COLOR N/A
 BODY FINISH Dark Bronze
 WATTAGE 15W
 DIMMER Low Voltage Electronic
 DIMENSIONS 4"W x 5"H
 INTEGRATED LED MODULE 1 x LED/15W/120-277V LED

Technical Information

APERTURE SHAPE Round
 CEILING TYPE Drywall with Trim
 FUNCTION Downlight
 LAMP LIFE 90 hours
 BEAM ANGLE 40°
 LAMP COLOR 3000K Warm Dim
 LUMENS/WATT 64.33
 LUMINOUS FLUX 965 lumens



Shown in dark bronze

Model	Beam	Lumens	CRP	Color Temp	CR	Finish	Reflector/Trim
R2FQ2T Round Trim	F 40° W 55°	965 1370	1775 1370	WD 3000K-1800K	90	DB DE HWT WT	Black Dark Bronze Honey Walnut Aluminum

Field changeable beam angle with reflectors provided
 (40 degree / 55 degree)
 Lumens based on 40 degree beam angle



CLICK TO VIEW PRODUCT

Notes: