

Lightology

lightology.com
866-954-4489
05-18-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362441**
 Approved On: _____ Approved By: _____

FQ 2 inch 25W Round Trimless New Construction Non-IC Housing By WAC Lighting



Description

The FQ 25 Watt 2 Inch Non-IC Rated Airtight New Construction housing is designed for trimless round trims. Ceiling cutout (Round): 3.5 inch diameter. Ceiling thickness: 1/2 to 1 inch. Universal 120/277 with Electronic Low Voltage (ELV): 100%-1% and TRIAC: 100%-1% dimming at 120V, or 0-10V: 100-1% dimming at 277V. NOTE: A complete fixture requires a housing and trim (round), sold separately.

Specifications

COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	17.37"W x 5.87"H x 10"D
INTEGRATED LED MODULE	LED/25W/120-277V LED


Technical Information

APERTURE SHAPE	Round
HOUSING HEIGHT	6"
HOUSING TYPE	New construction NON IC Airtight
CEILING TYPE	Drywall Trimless/Flush



Shown in galvanized steel

New Construction Trimless **R2FRNL** Round (Spackle frame included)



CLICK TO VIEW PRODUCT

Notes: