

Lightology

lightology.com
866-954-4489
04-25-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **DLS1374556**
 Approved On: _____ Approved By: _____

Excel Color-Select Fire Rated Recessed Panel Light

By DALS Lighting



Description

The Excel Fire Rated Recessed Panel Light features sleek, low-profile aluminum construction that is both stylish and practical for indoor and outdoor settings. Installation is easy, and the fixture can be daisy chained. Using edge-lit technology, LED light diffused by a frosted lens provides a smooth 360 degree wide spread of ambient illumination. Switch-selectable color temperature 2700K, 3000K, 3500K, 4000K, or 5000K with a switch inside fixture. TRIAC dimming (see attached manufacturer dimmer reference). 2-hour fire-rated without additional housing or hardware (in accordance with UL 263, ASTM E119, and CAN ULC S101) with UL L556 floor-ceiling assembly.

Specifications

COLOR	Frosted
BODY FINISH	White
WATTAGE	11W
DIMMER	Standard 120V
DIMENSIONS	5.06"W x 1.13"H
INTEGRATED LED MODULE	1 x LED/11W/120V LED
COUNTRY OF ORIGIN	China


Technical Information

APERTURE SHAPE	Round
HOUSING HEIGHT	2"
HOUSING TYPE	Remodel IC Airtight
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
COLOR RENDERING	80 CRI
LAMP COLOR	CCT Select
LUMENS/WATT	75.00
LUMINOUS FLUX	825 lumens




Shown in white / frosted

5004-FR-CC - Fire-Rated CCT 4" Round Panel Light



5006-FR-CC - Fire-Rated CCT 6" Round Panel Light



CLICK TO VIEW PRODUCT

Notes: