

# Lightology

lightology.com  
866-954-4489  
08-04-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG1389232**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Reveal Wall Wash 2 Tunable White Plaster-In LED System 24V

By PureEdge Lighting



### Description

The Reveal Wall Wash 2 is a 24VDC linear LED system that washes the wall from the very top of the ceiling to the floor. Features a shallow, plaster-in aluminum extrusion no thicker than drywall. Position the Reveal 24 inches away from the projected wall, position the LED strip within the channel, connect to a low voltage power supply, then plaster over the edges and paint to match surrounding surface. Dynamic Tunable White 2K6K grants independent control and adjustment of color temperature and intensity from 2000K (Sunset) through 6500K (Daylight). Sold in 1 foot increments up to 20 feet (5W), 12 feet (7W) or 10 feet (10W) and may be field-cut to any length. System includes junction box, adjustable mounting bars, Reveal Wall Wash channel(s), power feed end cap, junction box cover, dead end cap, take-up box, drywall screws, LED Soft Strip, and lens(es). Order additional Junction Box (RVWW2-1RE-JBOX) separately to rough-in electrical wiring before drywall installation, sold separately. NOTE: Required power supply and dimmer control sold separately.

### Specifications



COLOR . . . . . N/A  
BODY FINISH . . . . . Satin Aluminum  
WATTAGE . . . . . 5W  
DIMMER . . . . . N/A  
DIMENSIONS . . . . . 12"L x 3.63"W x 0.58"H  
INTEGRATED LED MODULE . . . . . 1 x LED/5W/24V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 92 CRI  
LAMP COLOR . . . . . 2000K-6000K Tunable White  
LUMENS/WATT . . . . . 56.60  
LUMINOUS FLUX . . . . . 283 lumens



Shown in satin aluminum



CLICK TO VIEW PRODUCT

Notes: