

lightology.com 866-954-4489 12-13-25

Project:													
Company:													
Location:	Fixture Type:												
SPEC #: <b>EDG1389376</b>													
Approved On:	Approved By:												

## Lazer Line Static White Up or Down Suspended System 24VDC By PureEdge Lighting







## Description

Lazer Line is a 24VDC direct or indirect (uplight or downlight) LED lighting system providing general illumination for architectural applications. The fieldcuttable single channel in 3 and 5 watts per foot is sold in 1 inch increments and allows a maximum length of 30 feet (3 watt) or 20 feet (5 watt) with power feed at one end and one non-power turnbuckle, or a maximum length of 60 feet (3 watt) or 40 feet (5 watt) with power feed turnbuckles at both ends. The 4 inch round turnbuckles allow Lazer Line to be positioned 0-90 degrees relative to the mounting surface, creating a 3-dimensional appearance. Mounts to standard 4 inch square junction box with round plaster ring. Paint canopy to blend into wall for a seamless look. Note: System includes Lazer Line channel and mounting hardware. System requires a Universal remote power supply (dimmable TRIAC/ ELV/0-10V), sold separately. Product is built to order.

## Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE 5 x LED/3W/24V LED

## Technical Information

LAMP LIFE																50	00	0 h	oui	'S
BEAM ANGL	Ξ.																		120	)°
COLOR RENI	DERI	N	ο.															. 9	CF	₹I
LAMP COLO	₹.																	. 24	-00	K
LUMENS/WA	TT																	. 4	21.6	7
LUMINOUS F	LUX															120	65	lun	ner	ıs



Shown in pure white / white





CLICK TO VIEW PRODUCT

Notes:	:			
--------	---	--	--	--