

lightology.com 866-954-4489 08-04-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1389543	
Approved On:	Approved By:

Lazer Line RGB+White Up+Down Suspended Lighting System By PureEdge Lighting





Description

Lazer Line is a 24VDC Direct/Indirect (uplight and downlight) LED Lighting System providing general illumination for architectural applications. The field-cuttable dual strip channel is sold in 1 inch increments with 10 watts per foot (4.4 watts up/4.4 watts down) with uplight in RGB (Red/ Blue/Green) color temperature and downlight in 2400K, 2700K, 3000K or 3500K. The 4 inch round turnbuckles allow Lazer Line to be positioned 0-90 degrees relative to the mounting surface, creating a 3-dimensional appearance. Mounts to standard 4 inch square junction box with round plaster ring. Paint canopy to blend into wall for a seamless look. Note: A DMX Dynamic color changing power supply is required and sold separately. DMX power supply must be used with PureEdge CDMX1-RGBW or CTP controller. System includes Lazer Line Channel (LZUD), Lazer Line Tape, and turnbuckles. Product is built to order

Specifications


COLOR																									N/A	4
BODY FINISH																					F	ur	e ۱	W	hite	е
WATTAGE																								. 5	OV	V
DIMMER																									N/A	4
DIMENSIONS																				6	0"	L×	0.	.44	í"V	V
INTEGRATED L	E	D	M	DE	DU	LE	Ξ									5	×	LI	ΕC)/1	٥١	N/2	24	VΙ	E)

Technical Information

LAMP LIFE															į	50000 hours
LAMP COLOR	2															RGB+White



Shown in pure white





CLICK TO VIEW PRODUCT

Notes:			