

lightology.com 866-954-4489 12-13-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1390880	
Approved On:	Approved By:

Lazer Line Tunable White Up+Down Suspended Lighting System By PureEdge Lighting



Description

Lazer Line is a 24VDC Direct/Indirect (uplight and downlight) LED Lighting System providing general illumination for architectural applications. The fieldcuttable dual strip channel is sold in 1 inch increments with 10 watts per foot (5 watts up/5 watts down) in Dynamic/Tunable White 2K6K (2000K-6500K) color temperature and downlight in a variety of color temperature options. System can be run up to 20 feet with power feed at one end, or 40 feet with power feeds at both ends. The 4 inch round turnbuckles allow Lazer Line to be positioned 0-90 degrees relative to the mounting surface, creating a 3-dimensional appearance. Mounts to standard 4 inch square junction box with round plaster ring. Paint canopy to blend into wall for a seamless look. Note: A DMX 2XK color changing power supply or 2XK 2-channel 0-10V power supply is required and sold separately. 0-10V power supply requires two dimmers -- one for intensity and one for color temperature. DMX power supply must be used with PureEdge controller. Product is built to order


Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
INTEGRATED LED MODULE

Technical Information



Shown in pure white





CLICK TO VIEW PRODUCT

Notes: