

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG140560	· ·
Approved On:	Approved By:

Cirrus R1 Linear Suspension w/Remote/End Feed/SQ Canopy By PureEdge Lighting







Description

The Cirrus R1 Lens End Feed Suspension with Remote 24VDC Power Supply (sold separately) and Square Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Features a diffused white rectangular lens with a 140 degree beam spread available in various increments from 36 to 420 inches, a variety of finishes, four wattage options, and a spectrum of color temperature options. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes a 4.6 inch square canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 96 inches. Lengths over 96 inches ship as two segments.

Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
INTEGRATED LED MODULE 3 x LED/2W/24V LED

Technical Information

LAMP LIFE .														į	50	00	0 h	ou	rs
BEAM ANGLE																		100)°
COLOR RENDE	RING																. 9	5 CF	RΙ
LAMP COLOR																	. 2'	700	K
LUMENS/WATT																	. 10	06.5	Ю
LUMINOUS FLU	JX .														2	213	lur	ner	าร



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT

Notes:
