

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG1405840	
Approved On:	Approved By:

PSBB RGBTW Power Supply with Bridgebox for Ceiling Linear By PureEdge Lighting











Description


The Pure Smart Wi-Fi PSBB RGBTW Power Supply for Ceiling Linear contains a Wi-Fi enabled WiZ Pro Type UR Bridgebox which allows for integration into the WiZ Pro Wireless control ecosystem. No hub required and provides 5 channel full color control of the TruColor RGBTW Light Engine. The WiZ App, WiZ Pro Dashboard, and Room Controllers (CWW-TW-SCENEWH and CWR-TW-SCENE-WH) from Pure Smart allow for dimming, CCT selection, grouping, scheduling, and the programming of preset and custom scenes. Voice control is available through integration with Amazon Alexa, Google Assistant, Siri Shortcuts, IFTTT, and SmartThings. Communicates via 2.4GHz Wi-Fi only. Accepts an input voltage in a range of 120-277V and outputs 24VDC power. Dims down to 5%. Integrated short circuit, overload, and thermal protection. Easily accessible external pushbutton allows for power cycling which triggers pairing mode to the connected smart device. The PSBB RGBTW Power Supply for Ceiling Linear is compatible with Cirrus Ceiling, Glide Ceiling, Nova Ceiling and Zipp Ceiling by PureEdge Lighting. NOTE:TC5W5 Power Supply: 5 Watts RGB and 5 Watts Tunable WhiteTC5W7 Power Supply: 5 Watts RGB and 7 Watts Tunable WhiteTC5W10 Power Supply: 5 Watts RGB and 10 Watts Tunable White

Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
BULB INCLUDED



Shown in white





CLICK TO VIEW PRODUCT

Notes:	