Lightology

lightology.com
866-954-4489
10-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1440083**

Approved On: Approved By:

# Flex Neon LRT7 Outdoor TruColor RGBTW 3-Sided Lens 24V


By PureEdge Lighting


## Description

Flex Neon LRT7 TruColor RGBTW bends left to right or right to left with a 0.7 inch wide three-sided lens, offering superior color quality and performance while creating uniform illumination without visible dots. Sold as 5W5: 5 watts RGB and 5 watts Tunable White up to 20 feet; or 5W7: 5 watts RBG and 7 watts Tunable White up to 12 feet. Features E (end power input wire), CA (cap at end, no feed through), and W (outdoor wet location barrel connector cable leads) with an IP67 rating for outdoor wet locations. Pure Smart TruColor technology uses five channels of tunable LEDs, composed of RGBTW red, blue, green, and Tunable White (1500K-6500K), giving customers access to the warm glow of the sunset (1500K-2400K golden hour) to the pure white light of the mid-day sun (5700K) and everything in between. Flex Neon is offered with both indoor and wet-rated junction boxes (sold separately), which include a Pure Smart/WiZ Pro Bridgebox allowing for 5-Channel, full color, wireless control of the TruColor RGBTW Light Engine with the WiZ Pro Software Suite or Pure Smart Wi-Fi Room Controller (sold separately). System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon).Note: System requires outdoor rated 24VDC RBGTW power supply for remote Bridgebox (PSBR-96W-24VDC), sold separately. Optional mounting accessories sold separately.Product is built to order



Shown in white




### Specifications

| | |
|---|---|
| COLOR | White |
| BODY FINISH | N/A |
| WATTAGE | 25W |
| DIMMER | N/A |
| DIMENSIONS | 60"L x 0.7"W x 0.75"H |
| INTEGRATED LED MODULE | 5 x LED/5W/24V LED |

### Technical Information

| | |
|---|---|
| LAMP LIFE | 50000 hours |
| BEAM ANGLE | 120° |
| COLOR RENDERING | 96 CRI |
| LAMP COLOR | RGB+White |
| LUMENS/WATT | 184.00 |
| LUMINOUS FLUX | 920 lumens |

CLICK TO VIEW PRODUCT

Notes: